

185 WATTS

DC4-185 SERIES DC-DC

FEATURES:

- RoHS Compliant
- 36-72 VDC Input
- Advanced SMT Design
- Compact 4.2" x 7.0" x 1.5" Size
- 2 Year Warranty
- One to Four Outputs
- 4242 VDC Reinforced Insulation
- Fits 1U Applications
- EN 60950-1 ITE Certification
- EN 60601-1 Medical Certification
- Size & Pin compatible with REL-185 Series
- Optional Chassis and Cover



OPEN CHASSIS



CHASSIS/COVER

SAFETY SPECIFICATIONS



Underwriters Laboratories
File E137708/E140259

UL 60950-1 2nd Edition
UL 60601-1 1st Edition



CB Certificate per IEC 60950-1:2005
2nd Edition +A1:2009 including all
National Deviations
CB Certificate per IEC 60601-1 (1988)
2nd Edition A1, A2



UL Recognition
Mark for Canada
File E137708/E140259

CAN/CSA-C22.2 No. 60950-1-07,
2nd Edition
CAN/CSA-C22.2 No. 601-1-M90
with updates 1 and 2



TUV

EN 60950-1/A1:2010
EN 60601-1/A2:1995

MODEL LISTING

MODEL	OUTPUT 1 ⁽⁸⁾	OUTPUT 2 ⁽⁸⁾	OUTPUT 3 ⁽⁷⁾	OUTPUT 4 ⁽⁷⁾
DC4-185-4001	+3.3V/20A ⁽¹⁾	+5V/10A	+12V/2A	-12V/2A
DC4-185-4002	+5V/20A ⁽¹⁾	+3.3V/10A	+12V/2A	-12V/2A
DC4-185-4003	+5V/20A ⁽¹⁾	+3.3V/10A	+15V/2A	-15V/2A
DC4-185-4004	+5V/20A ⁽¹⁾	-5V/10A	+12V/2A	-12V/2A
DC4-185-4005	+5V/20A ⁽¹⁾	-5V/10A	+15V/2A	-15V/2A
DC4-185-4006	+5V/20A ⁽¹⁾	+24V/3A	+12V/2A	-12V/2A
DC4-185-4007	+5V/20A ⁽¹⁾	+24V/3A	+15V/2A	-15V/2A
DC4-185-3001	+5V/20A ⁽¹⁾	+12V/5A		-12V/3A
DC4-185-3002	+5V/20A ⁽¹⁾	+15V/4A		-15V/3A
DC4-185-2001	+3.3V/20A ⁽¹⁾	+5V/10A		
DC4-185-2002	+5V/20A ⁽¹⁾	+12V/8A		
DC4-185-2003	+5V/20A ⁽¹⁾	+24V/4A		
DC4-185-2004	+12V/10A	-12V/6A		
DC4-185-2005	+15V/8A	-15V/5A		
DC4-185-1001	2.5V/37A ⁽²⁾			
DC4-185-1002	3.3V/37A ⁽²⁾			
DC4-185-1003	5V/37A ⁽²⁾			
DC4-185-1004	12V/15.4A			
DC4-185-1005	15V/12.3A			
DC4-185-1006	24V/7.7A			
DC4-185-1007	28V/6.6A			
DC4-185-1008	48V/3.8A			

NOTES

Consult factory for alternate output configurations.
Consult factory for positive, negative or floating outputs.
Refer to Applications Information for complete output power ratings.
All specifications are maximum at 25° C, 185W unless otherwise stated, may vary by model and are subject to change without notice.
Specify optional chassis and cover, power good or reverse input protection when ordering.

OUTPUT SPECIFICATIONS

Total Output Power at 50° C	135W	Convection Cooled
	185W	300 LFM Forced Air
Output Voltage Centering	Output 1: ± 0.5%	(All outputs)
	Output 2: ± 5.0%	at 50% load)
	Output 3: ± 5.0%	
	Output 4: ± 5.0%	
Output Voltage Adjust Range	Output 1: 95 - 105%	
Load Regulation	Output 1: 0.5%	(10-100% load change)
	Output 2: 5.0%	(20-100% load change)
	(4001,4,5,2001) 10.0%	(20-100% load change)
	(4002,3) 15.0%	
	Output 3: 5.0%	
	Output 4: 5.0%	
Source Regulation	Outputs 1 - 4: 0.5%	
Cross Regulation	Outputs 2 - 4: 6.0%	
Output Noise	Outputs 1 - 4: 1.0%	
Turn on Overshoot	None	
Transient Response	Outputs 1 - 4	
Voltage Deviation	5.0%	
Recovery Time	500µS	
LOAD CHANGE	50% TO 100%	
Output Overvoltage Protection	Output 1: 110% to 150%	
Output Overpower Protection	110-160% rated Pout, cycle on/off, auto recovery	
Start Up Time	5 Seconds	

INPUT SPECIFICATIONS

Input Voltage Range	36-72 VDC
Input Under-Voltage Lockout	
Turn-On Voltage	29.0-35.0 VDC
Turn-Off Voltage	28.0-34.0 VDC
Input Overvoltage Shutdown	77.0-85.0 VDC
Maximum Input Current	7.0 A
Reflected Ripple Current	5 %
Efficiency	84% Typ., Full Power, 48VDC, varies by model


ENVIRONMENTAL SPECIFICATIONS

Ambient Operating	0° C to + 70° C
Temperature Range	Derating: See Power Rating Chart
Ambient Storage Temp. Range	- 40° C to + 85° C
Temperature Coefficient	Outputs 1 - 4: 0.02%/°C

GENERAL SPECIFICATIONS

DIELECTRIC STRENGTH ⁽¹⁰⁾	
Reinforced Insulation	4242 VDC, Primary to Secondary, 1 Sec.
Basic Insulation	2121 VDC, Primary to Ground, 1 Sec.
Operational Insulation	707VDC, Secondary to Ground, 1 Sec.
Power Good Signal	Logic high with input voltage above Vin min.
Remote Sense (singles only)	250mV compensation of output cable losses
Mean-Time Between Failures	100,000 Hours min., MIL-HDBK-217F, 25° C, GB
Weight	1.28 Lbs. Open Frame
	2.16 Lbs. Chassis and Cover







MAXIMUM OUTPUT POWER VS. AMBIENT TEMPERATURE



INTEGRATED

POWER DESIGNS 300 Stewart Road ■ Wilkes-Barre, PA 18706 ■ Phone: (570) 824-4666 ■ Fax: (570) 824-4843 ■ Email: sales@ipdpower.com ■ Web: www.ipdpower.com

DC4-185 SERIES MECHANICAL SPECIFICATIONS



APPLICATIONS INFORMATION

- Rated 15A maximum with convection cooling.
- Rated 27 A maximum with convection cooling.
- Total power must not exceed 135 watts with convection cooling on open frame models except where noted.
- Total power must not exceed 185 watts with 300 LFM forced air cooling on open frame models.
- Total power must not exceed 110 watts with convection cooling and chassis/cover option.
- Total power must not exceed 185 watts with 300 LFM forced air cooling and chassis/cover option.
- Total current from Outputs 3 & 4 must not exceed 3 amps with convection cooling.
- Total current from Outputs 1 & 2 must not exceed 20 amps with convection cooling.
- Semiconductor case temperatures must not exceed 110° C.
- Each output can deliver its rated current but total output power must not exceed maximum power as determined by the cooling method stated above.
- Sufficient area must be provided around convection cooled power supplies to allow natural movement of air to develop.
- 300 linear feet per minute of airflow must be maintained one inch above any point of the heatsink in the direction shown when forced air cooling is required.
- This product is intended for use as a professionally installed component within information technology and medical equipment.
- A minimum load of 10% is required on output one to ensure proper regulation of remaining outputs.
- Remote sense terminals may be used to compensate for cable losses up to 250mV (single output models only). The use of a twisted pair is recommended as well as a decoupling capacitor (0.1 - 10µF) and a capacitor of 100µF/amp connected across the load side.
- Peak to peak output ripple and noise is measured directly at the output terminals of the power supply, without the use of the probe ground lead or retractable tip, 20 MHz bandwidth.
- This product was type tested and safety certified using the dielectric strength test voltages listed in Table V of UL 60601-1. In consideration of Clause 20.4g, care must be taken to insure that the voltage applied to a reinforced insulation does not overstress basic insulation. Secondary to ground capacitors may need to be removed prior to performing a dielectric strength type test on the end product. It is highly recommended that the DC test voltages listed in DVB.1, Annex DVB are not exceeded during a production-line dielectric strength test of the assembled end product. Please consult factory for further information.
- This power supply has been safety approved and final tested using a DC dielectric strength test. Please consult factory before performing an AC dielectric strength test.
- Maximum screw penetration into bottom chassis mounting holes is .100 inches.
- Maximum screw penetration into side chassis mounting holes is .250 inches.
- To meet emissions specifications, all four mounting hole pads must be electrically connected to a common metal chassis. Chassis/cover option recommended.

CONNECTOR SPECIFICATIONS

P1	DC Input	#6 standard (3) position terminal block.
P2	DC Output (Single)	6-32 screw down terminal mates with #6 ring tongue terminal. (10 in-lb max)
P2	DC Output (Multiple)	.156 friction lock header mates with Molex 09-50-3161 or equivalent crimp terminal housing with Molex 2478 or equivalent crimp terminal.
G	Ground	.187 quick disconnect terminal.
P3	P.G./Sense (Single)	.100 breakaway header mates with Molex 50-57-9008 or equivalent crimp terminal housing with Molex type 71851 or equivalent crimp terminal.
P3	P.G./Sense (Multiple)	.100 breakaway header mates with Molex 22-55-2081 or equivalent crimp terminal housing with Molex type 71851 or equivalent crimp terminal.

RECOMMENDED AIR FLOW DIRECTION

- 1 – Optimum 2 – Good 3 – Fair